



SPECIFICATION:

- 1). Driving: Duty:1/32, Bias:1/5, Vdd:5.0V, Vlcd:4.6V
- 2). VIEWING DIRECTION: 6 O'CLOCK
- 3). Display mode: STN/Positive/Transflective/YG
- 3). Operating temp.: 0°C~+50°C
- 4). Storage temp.: -10°C~+60°C
- 5). Control IC: SBN1661G(Or Compatible)
- 6). BACKLIGHT: EDGE, YG
- 7). DIMENSIONS WITH MARK "*" ARE IMPORTANT WITH MARK "(" ARE REFERENCED
- 8). All the raw materials are RoHS compliant

PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
SYMBOL	VDD	VSS	V0	RST	E1	E2	R/W	A0	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	BLA	BLK

REVISION RECORD		REV
First issue		A0



深圳市三元晶科技有限公司
ShenZhen TCC LCD Hi-Tech Co., Ltd

MODEL NO.	SYB12232A1V10-5C13YL3R-B5NG	GENERAL TOL: ± 0.3
APPROVED BY	CHECKED BY	DRAWING BY

PAGE?	1	OF	1	UNIT:	mm
PROJECTION					